

SMART 10TM

Engineered Timber Studs



- Available un-treated or H2s preservative treated
- Product Technical Statement (NCC part A5.2(1)(f)) available on request
- AS 2754 Type B bond – suitable for Service class 1 and 2
- Long term sustainability

Characteristic Property		SMART 10 [®]	MGP 10
Stiffness	E MPa	10,000	10,000
Bending	f'_b MPa	38	17
Compression parallel to grain	f'_c MPa	35	18
Compression perp to grain	f'_p MPa	10	10
Shear	f'_s MPa	4.8	4.2
Joint strength group		JD4	JD5 Heart in JD4 FOH



www.tilling.com.au
Sales 1800 33 77 03
Technical 1300 66 86 90



The information contained in this product document is current as at May 2021 and is based on data available to Tilling Timber Pty Ltd at the time of going to print. Tilling Timber Pty Ltd has used its reasonable endeavours to ensure the accuracy and reliability of the information contained in this document and, to the extent permitted by law, will not be liable for any inaccuracies, omissions or errors in this information nor for any actions taken in reliance on this information. Tilling Timber Pty Ltd reserves the right to change the information contained in this document without prior notice. It is important that you call the Tech Support customer Helpline on 1300 668 690 to confirm that you have the most up to date information available.

© 2021 Tilling Timber Pty Ltd ABN 92 004 621 121 Date of publication May 2021 SmartFrame is a Registered Trademark of Tilling Timber